SINGLE ANCHOR POINTS ON SANDWICH PANEL ROOF

RAP GLOBE

SINGLE ANCHOR POINTS, LIKE THE RAP GLOBE, ARE PERMANENT ANCHORS INSTALLED ON THE SURFACE OF A STRUCTURE AND ARE SUITABLE FOR ONE USER AT A TIME. THE USER IS SECURED DIRECTLY TO THE 360^0 ROTATING SAFETY EYE OF THE ANCHOR POINT ITSELF.

Installation
RAP Globe anchor points are installed to sandwich panels with a steel top layer, with a minimum thickness of 0,5 mm (25 gauge), by means of the aluminum XSMD base plate. In this case installation occurs with twelve Gesipa 7,7 mm (5/16") bulb-tite rivets.

All XSPlatforms single anchor point systems are designed, tested and certified in accordance to the latest European standards EN 795:2012 type A.

SPECIFICATIONS

- Steel trapezoidal cold roof plates
- Min. thickness of 0,63 mm (24 gauge)
- Clamping installation method
- Max. roof pitch of 10°
- Anchorage eye with 360° rotation
- Suitable for 1 user
- Suitable for both fall arrest and fall restraint
- Durable stainless steel components
- EN 795:2012 type A

XSPlatforms®

Papland 11, P.O. Box 510.
4200 AM Gorinchem,
The Netherlands

Tel. +31 183 569 111
Fax +31 183 569 112

info@xsplatforms.com
xsplatforms.com